



## Standalone MONOline 1100

for monitoring of C3H8



### Features

- The MONOline monitor displays the detector gas concentration with name and alarm status
- The MONOline is factory calibrated and ready to use. Other measuring ranges are available on request
- 24VDC or 230VAC power supply
- Internal sounder alarm
- Clearly visible flashing LED beacon alarm
- Alarm status clearly visible on the OLED-Display
- 3 internal relays available to activate ventilation fans or alarming units
- Different relay functions programmable (Reset manual or automatic, NO/NC) and alarm thresholds by magnet pen
- Different relay functions programmable (Reset manual or automatic, NO/NC) and alarm thresholds by magnet pen
- Electrochemical sensor technology with simple concept for replacing a sensor
- Different relay functions programmable (Reset manual or automatic, NO/NC) and alarm thresholds by magnet pen
- Different relay functions programmable (Reset manual or automatic, NO/NC) and alarm thresholds by magnet pen
- integrated MODBUS RTU interface
- Connector for remote RESET
- Robust IP 65 enclosure
- Product has been developed by KIMESSA and is manufactured in Switzerland


## Standalone MONOline 1100

Gas:	Hydro Carbon
Gas formula:	HC
Alarm thresholds:	2 free programmable per gas detector
Warranty:	12 month warranty
Position:	

## Sensor specifications

Measurement principle:	Infrared
Measuring range:	0...5000 ppm/ 0...100 % LEL
Standard calibration:	0...100 % UEG
Response time $t_{90}$ :	< 90 sec
Operating temperature:	-30 °C ... +50 °C
Start up after reconditioning:	approx. 1 hour
Pressure range:	atmospheric $\pm$ 10%
Air humidity:	15...90 % R.H. non-condensing
Position sensitivity:	none
Long term output drift:	< 2% signal loss/month
Life span at 20 °C:	6-8 years, depending on the application

## Electronic and Dimensions



## Housing

Housing protection:	IP 65
Material:	Thermoplast
Weight:	820 g

## Specifications electronic

Wiring analogue:	3x 0,75 mm <sup>2</sup> , shielded
Wiring digital:	4x 1,0 mm <sup>2</sup> , shielded
Supply:	230 VAC/ 24 VDC
Power consumption:	max. 200 mA
Output signal analogue:	4...20 mA / 0...20 mA
Output signal digital:	KIMESSA CANBUS / Modbus RTU
Switching output:	3 potential free (2A)

## Specifications construction

Cable gland:	cable bushing plate
Cable entry:	unten
Tests:	CE
Display:	OLED-Display
Position:	depending on display
RESET-Connector:	yes
Volume:	92 dB
Optical alarm:	incorporated LED flash light

## Inspection (Maintenance)

The sensor and the electronic require an inspection. Routine calibration is recommended once or twice a year.